

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 April 2005 (28.04.2005)

PCT

(10) International Publication Number
WO 2005/038314 A1

(51) International Patent Classification⁷:
F24D 19/00

F16K 3/26 //

(74) Agent: ZACCO DENMARK A/S; Hans Bekkevolds Allé
7, DK-2900 Hellerup (DK).

(21) International Application Number:
PCT/DK2004/000712

(22) International Filing Date: 18 October 2004 (18.10.2004)

(25) Filing Language: Danish

(26) Publication Language: English

(30) Priority Data:
PA 2003 01523 16 October 2003 (16.10.2003) DK

(71) Applicant (for all designated States except US): FLOW-
CON INTERNATIONAL A/S [DK/DK]; Kongstedsvej 2,
DK-4200 Slagelse (DK).

(72) Inventor; and


(75) Inventor/Applicant (for US only): MOESBY, Peter
[DK/DK]; Mandøvej 6, DK-4200 Slagelse (DK).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]


(54) Title: AN ADJUSTABLE REGULATOR INSERT WITH LINEAR SETTING/FLOW CHARACTERISTIC



(57) Abstract: An adjustable regulator insert (2) for valves (1), in particular for controlling the liquid flow in a plant for central heating or air conditioning. The insert (2) comprises inflow openings (8) and outflow openings (9), wherein the outflow openings (9) are closed off in response to the difference in pressure across the insert (2) under the influence of a spring (15) that seeks to keep the outflow openings (9) open. The insert (2) is furthermore provided with means for adjustably closing off the inflow openings (8). The insert (2) is configured such that a certain degree of adjustable closure of the inflow openings (8) entails a compression of the spring (15) which is inversely proportionate with the closure. Hereby an approximately linear equilibrium between the degree of closure of the inflow openings 8 and the flow through the insert (2) is accomplished.

WO 2005/038314 A1

WO 2005/038314 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report